



Industrial monitor – OPD8000 series

Proven display quality made in Germany

OPD8000 series monitors have been deployed in countless industrial production applications for many years. The popular HMI monitors with their capacitive touchscreens enable processes to be clearly visualised while at the same time being reduced to the essentials. Drag, swipe, rotate, zoom – it's all easy and intuitive with multi-finger operation.



Everything clearly in view

- > Screen sizes: 17.3 or 23.8 inches in Full HD resolution
- > Multi-touch display with tempered glass panel
- > Operable with glove
- > IP65-rated front protection

All the power you need: even over 100 metres.

The hygienically designed monitor also works well over longer distances. The optionally integrable HDBaseT receiver module makes it possible to transmit multimedia signals such as image and touch control over distances of up to 100 metres – via one single cable.

Technical data



		OPD8017	OPD8024	
Display	Resolution	17.3" LED backlight 1920 x 1080 pixels	23.8" LED backlight 1920 x 1080 pixels	
Touch		PCAP multi-touch, 3 mm glass, hardened and non-reflecting		
Housing		Galvanised sheet metal housing		
Interfaces		1 x HDMI, 1 x DisplayPort 3 x USB 2.0 1 x USB 2.0 Slave		
Power adapter		Nominal voltage 12 - 48 VDCIN (tolerance: 9 - 60 VDCIN)		
Protection class		IP65 front, IP20 back (not verified from UL, tested through ADS-TEC)		
Vibration		EN 60068-2-6 3M5 (according 60721-3-3)		
Shock		EN 60068-2-27 3M5 (according 60721-3-3)		
Humidity		10 to 85 %, non-condensing		
Operating temperatur		0 °C to + 50 °C	0 °C to + 45 °C	
Dimensions (W x H x D)		433 x 263 x 72 mm	580 x 349 x 72 mm	
		422 x 252 mm	569 x 338 mm	
Installation depth		83 mm		
Gewicht		4.5 kg	7.8 kg	

ads-tec Industrial IT GmbH 72622 Nürtingen Phone +49 70222522-200 Fax +49 70222522-402 sales@ads-tec.de



www.ads-tec-iit.com/en