

Model Information



■ Main Features

- USB 2.0 to 4 x RS232 ports
- High-Speed serial ports 460.8kbps
- Driver for Windows, Linux, Mac OS X
- LEDs for Power/Ready and TxD/RxD activity
- ESD protection on USB and serial ports
- Bus powered
- Ruggedized metal housing
- DIN-Rail and wall mount options
- Wide range of operating temperatures

[Contact Online...](#)

USB-4COM ECO (USB-4COM-M)

Quick Link: | [Main Features](#) | [More Pictures](#) | [Overview](#) | [USB Interface](#) | [Serial Interface](#) | [Software](#) | [Power Requirement](#) | [Housing and Mounting](#) | [Environmental Data](#) | [Standards](#) | [MTBF \(Mean Time Between Failures\)](#) | [Warranty](#) | [Ordering Information](#) | [Options](#) | [6695](#) | [Packaging](#) |

■ More Pictures



Click on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

The USB-4COM ECO provides easy serial port expansion over USB 2.0 connecting to high speed RS232 devices. All USB-xCOM Eco converters are fully ESD and surge protected, bus powered and accommodated in a small metal case. Furthermore, it can operate across a large range of temperatures to cope with harsh operating conditions. Lastly, DIN-Rail and wall-mounting options are available.

Easy Serial Ports Configuration

The serial ports support all 9 signals of RS232 protocol. LEDs for PWR, RDY and TxD/RxD for each port clearly show the activity status for the user. Com Port drivers are available for Windows, Linux and Mac OS X. "USBCOM Configuration Utility" allows easy access to special Windows driver options to optimise settings and performance.

High Speed Rates and ESD Protection

USB 2.0 full speed connection allows serial data rates of up to 460.8kbps. Every non-standard bitrate (e.g. 31250bps MIDI) can easily be set up. USB-xCOM ECO systems are fully ESD protected at the USB and serial port interfaces.

■ USB Interface

USB-Input	USB 2.0 High Speed, USB 1.1 compliant
Connector	USB type B
Circuits	FTDI FT4232H Genesys GL850G

[>Back to top](#)

■ Serial Interface

No. of Ports/Type	4 x RS232
Connector	DB-9 male

Protection	16kV ESD surge protection
Signals non-ISO	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data Bits	7, 8
Stop Bits	1, 2
Parity	None, Even, Odd, Mark, Space
Flow Control	RTS/CTS, XON/XOFF
Baudrate	180bps - 460.8/500kbps
LEDs	TxD/RxD for each port

[>Back to top](#)

■ Software

Drivers	<ul style="list-style-type: none"> • Windows 2000 to Windows 10 (x86 and x64) • Windows Server 2000 to 2016 (x86 and x64) • Linux (Kernel 3.4 and later built-in) • Mac OS X
Installation	The driver is already installed (Linux), or installs by automatic Download after Device connection (Windows).

[>Back to top](#)

■ Power Requirement

Input Voltage	5V (USB)
Power Consumption	max 250mA, 1.25W
Connector	USB Type B, bus powered, no external supply

[>Back to top](#)

■ Housing and Mounting

Case	0.8mm sheet metal
Weight	150g, w/h box 0.6kg
Dimensions	108×129×25 mm ³ (W×L×H)
Packaged	155×168×58 mm ³
Mounting	Desktop use <ul style="list-style-type: none"> • DIN-Rail (optional) • Wall mount (optional)

[>Back to top](#)

■ Environmental Data

Operating Temp	-25°C - 75°C
Storage Temp	-30°C - 85°C
Ambient Humidity	5-95% non condensing

[>Back to top](#)

■ Standards

Declarations	CE, FCC
EMI	<ul style="list-style-type: none"> • EN 55022 Class B • 47 CFR FCC Part 15 Subpart B
EMS (EN 55024)	<ul style="list-style-type: none"> • EN 61000-4-3: Radiated RFI • EN 61000-4-4: Electrical Fast Transient • EN 61000-4-5: Surge • EN 61000-4-6: Induced RFI • EN 61000-4-8: Power Frequency Magnetic Field • EN 61000-4-11: Power supply dips
ESD	EN 61000-4-2 4kV contact 8kV air for <ul style="list-style-type: none"> • Serial Ports • USB

[>Back to top](#)

■ MTBF (Mean Time Between Failures)

MTBF	39.4 Years @ 25°C 22.7 Years @ 45°C	>Back to top
Standard	Telcordia (Bellcore) Standard; RelCalc. 5.0 BELL-7	>Back to top
■ Warranty		
Warranty Period	2 years	>Back to top
■ Ordering Information		
621	USB-4COM ECO (4x RS232)	>Back to top
■ Options		
■ 6695		
6693	WK-NCP Wallmount kit	
661	Serial Null-Modem adapter 9PF-9PF, change male to female	>Back to top
■ Packaging		
Packing list	<ul style="list-style-type: none"> • USB-4COM ECO device • USB 2.0 High-Speed cable • 4 rubber feet for table mode 	>Back to top

* Specifications are subject to change without notice.

* All trademarks and brands are property of their rightful owners.

USB-4COM ECO

[>Back](#)



USB-COM Plus Configurator

[>Back](#)

VScom USB-COM Plus Configurator
— □ ×

File Help

Present COM-Ports Show disconnected devices

COM3
 COM4
 COM6

Port Settings

Min. Read Timeout (ms):

Min. Write Timeout (ms):

Polling Period:

Latency Timer:

Serial Enumerator

Serial Printer

Cancel If Power Off

Event On Surprise Removal

Set RTS On Close

Disable Modem Ctrl At Startup

Global Settings

Ignore Hardware Serial Number

VScom USB-COM 232, SN: DN6NP3AA, ID: 4036015, LocalID: 31; Open COM Ports: 0

DIN-Rail Kit

[>Back](#)



Wall Mount Plates

[>Back](#)



(2021 Mar 19)