

Model Information



■ Main Features

- Industrial VPNRouter with Firewall, NAT & DNS
- Secure remote access with VPN tunnel
- VPN with SSL/TLS and AES-256
- Easy network setup using SimpleVPN
- Supports Ethernet, WLAN and 3G/4G
- Rich connectivity: LANs, COMs, USBs
- ESD surge protection
- Low Power, fanless, secure connectors
- Operating temperature range: -20°C - +65°C
- DIN RAIL /Wall mountable
- Robust metal case

[Contact Online...](#)

VPNRouter iR 2110

Quick Link: | [Main Features](#) | [More Pictures](#) | [Overview](#) | [SimpleVPN](#) | [Software](#) | [System](#) | [Serial Ports](#) | [Wireless interface \(option\)](#) | [Power Requirements](#) | [Housing and Mounting](#) | [Environmental Data](#) | [Standards](#) | [MTBF \(Mean Time Between Failures\)](#) | [Warranty](#) | [Ordering Information](#) | [Options](#) | [Packaging](#) |

■ More Pictures



Click on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

The VPNRouter iR 2110 is an advanced industrial VPN router designed for security sensitive network applications. The product's main feature includes the easy setup of secure VPN connections (SSL/TLS and AES-256 based) to other remote VPNRouters. The VPNRouter can act as the central firewall/router to the Internet or as a VPN gateway within an existing local network. In both roles, the VPNRouter can be a server or a client for the VPN. With the VPNRouter, one can significantly reduce costs as remote management and monitoring of critical assets is made possible. Examples of such assets include power and water treatment stations, production lines, ATMs, CCTVs and many other M2M applications.

Basic Router Services

The VPNRouter software is based on OpenWrt, which complies with all industrial high security standards. Over the browser based web front-end, the user can easily configure all network services including DHCP, DNS, NTP, UPnP and Firewall. Furthermore, it has the following security features:

- openVPN provides secure communication tunnels, using encryption of all IP packets and sender authentication whenever users access a private network over the public Internet.
- The firewall controls traffic between various trust zones shielding the private network from unauthorized outside access such as NAT.

Rich connectivity

WLAN 802.11b/g/n is available as a common option; two locations for SMA-antenna sockets are provided. The balanced variety of interfaces like LAN, USB, RS232/422/485 serial port enable VPNRouter iR 2110 to act as an economic but powerful gateway between networks and various

industrial devices and field busses. The USB port enables firmware update or transferring VPN configuration files.

Easy VPN deployment with SimpleVPN

SimpleVPN software enables a simple and comfortable OpenVPN configuration of all VPNRouters, whether they are used as Servers or Clients. The VPN setup of the whole can be fully configured by a single VPNRouter: Once a configuration of a VPNRouter is done, it can then easily be exported to other VPNRouters within the network with the use of either a USB-Stick, a configuration file or Ethernet cables. SimpleVPN supports common VPN standards such as OpenVPN. The level of simplicity that comes with the handling of necessary encryption keys and certificates, which can be created on the device itself, makes it easy and convenient for the user to establish a VPN tunnel network.

Rugged Hardware

The industrial VPNRouter series stands out due to their robust and compact design. VPNRouters are fanless, have small footprint and are DIN Rail mountable systems. They are fully ESD and surge protected, complying with IEC 61000-4-2 (8kV air and 4KV contact). Properties such as low power consumption (3W typical), an extended temperature range (-20°C to +65°C) and a wide range power supply (12-50V DC) make them ideal for harsh industrial environments. The options of WLAN and GSM/3G/4G modems for installations on mobile platforms exist. The MTBF of 13 years at 45°C environments shows the high technological reliability of VPNRouter series.

■ SimpleVPN

Functionality	SimpleVPN implemented in to VPN Routers can create a network of VPN tunnels. The network has star topology: all Client Routers (in Branches or Home Offices) connect to one central Server Router (in the Head Office). The Server acts as a central Hub/Switch for all data transfers: each PC in an office communicates with any other PC in other offices over the Server/Router. Changes in the configuration of Clients are easily done on the Server.
Security	Based on OpenVPN with SSL/TLS and AES-256
No. of VPN Tunnels	Depends on Internet connection Max. 5 Clients per Server in typical applications More Clients are possible with low data transfer demand
Management	The VPNRouter acting as Server allows the configuration of all Clients. Transferring the configuration to other clients can be done via <ul style="list-style-type: none">• USB-Stick• File Upload / Download• Ethernet cable (before deploying the Client Routers)
Keys / Certificates	Generated locally on the VPNRouter, or upload them from another reliable source
Device Roles	Router Role: In this mode the VPN Router can be configured as Router providing access to the Internet via Ethernet, 3G/4G Modem or WLAN. Ethernet supports xDSL, TV-Cable or fiber. The VPN tunnels are supported on all types of media. Internet and VPN access is granted to the local LAN ports, behind the built-in Firewall. Gateway Role: A VPN Router is placed into an existing company's local network, creating a VPN Gateway for IP addresses connected by VPN tunnels. PCs and other Devices in the local network use this Router as a Route to access the other offices.
Remote Access / Remote Service	The integrated software services also allow secure VPN connections to machines and devices with serial ports, CAN Bus interfaces, facilitating smart remote control of these interfaces on the VPN Routers. Using VSCAN API for CAN-Bus, RFC 2217 for serial ports and Modbus/TCP for Digital I/O full remote access to the machines is enabled in a very convenient way. Machines and devices with LAN interfaces are remote connected via LAN ports of the VPN Router.

[>Back to top](#)

■ Software	
Networking Services	Firewall with NAT, DHCP and DNS NTP, Dynamic DNS, UPnP
Interface Services	These interfaces allow remote access <ul style="list-style-type: none"> Serial Port RS232/RS422/RS485 via RFC 2217 and Telnet
>Back to top	
■ System	
Hardware	<ul style="list-style-type: none"> ARM Cortex-A8 RISC CPU @ 600MHz 256MB DDR3 Real time clock with battery backup
Mass Storage	<ul style="list-style-type: none"> 256MB NAND Flash memory SD 2.0 / SDHC microSD-card slot
Network	<ul style="list-style-type: none"> 1x 1000/100/10 Mbps Gigabit Ethernet 1x 100/10 Mbps Fast Ethernet WLAN 802.11b/g/n (optional) 2 x SMA antenna sockets available
Serial Peripherals	<ul style="list-style-type: none"> 1x USB 2.0 Host 1x RS232/422/485 high speed
LED	<ul style="list-style-type: none"> 1x Power, 1x WLAN, 1x Application LAN: 2x Link and Speed COM: TxD and RxD
DIP Switch	4 x switches for user's application
>Back to top	
■ Serial Ports	
Features	<ul style="list-style-type: none"> 1x RS232/422/485 Highspeed UART, 64 Byte FIFO (16C750) RS232: up to 921.6/1000 kbps RS422/485: up to 3.7 Mbps
Available Modes	Configured by Software <ul style="list-style-type: none"> RS232 RS422 full duplex RS485 4-wire, full duplex RS485 2-wire, half duplex, without echo
Signals	<ul style="list-style-type: none"> RS232: TxD,RxD, RTS,CTS, DTR,DSR, DCD, RI, GND RS422: Tx+/-, Rx+/-, GND RS485 2-wire: Data+/-, GND RS485 4-wire: Tx+/-, Rx+/-, GND
RS485 Data Direction Control	Driver Automatic via RTS
>Back to top	
■ Wireless interface (option)	
Standards	2.4GHz Radio, supports IEEE Std. 802.11b/g/n
WLAN Modes	Access Point (AP) or Client (Station)
TX Power	802.11b: <ul style="list-style-type: none"> Typ. 15.5dBm ±1.5 dBm @ 1Mbps (DSSS) Typ. 15.5dBm ±1.5 dBm @ 11Mbps (OFDM) 802.11g: <ul style="list-style-type: none"> Typ. 15.6dBm ±1.5 dBm @ 6Mbps (CCK) Typ. 13.5dBm ±1.5 dBm @ 54Mbps (OFDM) 802.11n: <ul style="list-style-type: none"> Typ. 13.4dBm ±1.5 dBm @ 6.5Mbps (OFDM) Typ. 13.3dBm ±1.5 dBm @ 150 Mbps(OFDM)

RX Sensitivity	802.11b: -95.6dBm @ 1Mbps, -88dBm @ 11Mbps 802.11g: -91.3dBm @ 6Mbps, -74.2dBm @ 54 Mbps 802.11n: -88.8dBm @ 6.5Mbps (20 MHz), -72dBm @ 72.2Mbps (20 MHz)
Transmission Rate	802.11b: 11Mbps 802.11g: 6 to 54Mbps 802.11n: 6.5 to 150Mbps
Transmission Distance	Up to 100m in open areas
Wireless security	<ul style="list-style-type: none"> • WEP • WPA • WPA2 • WPA2-Enterprise (IEEE 802.1X/RADIUS)
Antenna Connector	RP (Reverse-Polarity) SMA
>Back to top	
■ Power Requirements	
Input Voltage	9 – 54V DC
Power Consumption	<ul style="list-style-type: none"> • 0.2A @ 12V minimal • 0.3A @ 12V typical, plus devices on USB
Connector	3-pin Terminal Block
>Back to top	
■ Housing and Mounting	
Case	0.8mm sheet metal
Weight	w/o box 250g; w/h box 500g
Dimensions	115×73×25 mm ³ (W×L×H)
Packaged	150×107×48 mm ³
Mounting	<ul style="list-style-type: none"> • DIN Rail (option) • Wall mount (option)
>Back to top	
■ Environmental Data	
Operating Temp	-20°C – 65°C
Storage Temp	-30°C - 85°C
Ambient Humidity	10-85% non-condensing
>Back to top	
■ Standards	
Declarations	CE, FCC
EMI	<ul style="list-style-type: none"> • EN 55022 Class B • EN 61000-3-2: Limits of harmonic current emissions • EN 61000-3-3: Limitation of voltage changes • 47 CFR FCC Part 15 Subpart B
EMS (EN 55024)	<ul style="list-style-type: none"> • EN 61000-4-3: Radiated RFI • EN 61000-4-4: Electrical Fast Transient • EN 61000-4-5: Surge • EN 61000-4-6: Induced RFI • EN 61000-4-8: Power Frequency Magnetic Field • EN 61000-4-11: Power supply dips
ESD	EN 61000-4-2 4kV contact 8kV air for <ul style="list-style-type: none"> • Serial Port • USB • Ethernet • DC Power connector

[>Back to top](#)

■ MTBF (Mean Time Between Failures)

MTBF	39.0 Years @ 25°C 13.0 Years @ 45°C
Standard	Telcordia (Bellcore) Standard; RelCalc. 5.0 BELL-7

[>Back to top](#)

■ Warranty

Warranty Period	2 years
------------------------	---------

[>Back to top](#)

■ Ordering Information

6863	VPNRouter iR 2110
-------------	-------------------

[>Back to top](#)

■ Options

6031	Power adapter 110-230V AC to 12V @1A, DC, EU plug
6034	Power adapter 110-230V AC to 12V @1A, DC, US plug
6689	WLAN Kit internal internal module 802.11b/g/n, pigtail and antenna Purchase time option, not for later retrofitting
6692	DK-NCP DIN-Rail mounting kit
6693	WK-NCP Wallmount kit

[>Back to top](#)

■ Packaging

Packing list	<ul style="list-style-type: none">• VPNRouter system iR 2110• Printed Quick Installation Guide• Terminal block for Power Supply
---------------------	---

[>Back to top](#)

- * Specifications are subject to change without notice.
- * All trademarks and brands are property of their rightful owners.

VPNRouter iR 2110

[>Back](#)



External WLAN (demonstrated on Baltos iR 2110)

[>Back](#)



(2018 Jan 17)